



SELF-CONTAINED EMERGENCY TWIN LIGHT

... is designed with low EMI and specially equipped with a customised proprietary Hybrid IC for higher reliability and greater efficiency in operation. Compact and lightweight. Easy to install. Portable, allows flexibility in usage. Adjustable twin lamp allows flexibility in angle of projection.

Suitable for Shop, Supermarkets, Schools, Banks, Offices, Restaurants, Hospitals, etc.



ETL 210

IP 20



**HYBRID IC CONTROLLED SELF-CONTAINED
EMERGENCY TWIN LIGHT**


TECHNICAL CHARACTERISTICS

INPUT VOLTAGE	: 230Vac or 115Vac 50/60Hz \pm 10% or others A: 0.03 PF: 0.86
BATTERY	: 6V 4.5AH/7AH/10AH Sealed Lead Acid or 6V 4.5AH/8AH High Temp Rated Nickel Cadmium cells or others
LAMP USED	: 2 x 5W/10W Halogen or others
RATED PERIOD	: > 1 hr, 2 hrs, 3 hrs or others
MODE	: Non-maintained
POWER CONSUMPTION	: < 6VA
CHARGE MONITOR	: Super bright Green LED 5mm \varnothing
RECHARGE PERIOD	: 16 ~ 24 hrs
EMERGENCY LUMINANCE	: 45 Lumen
ELECTROMAGNETIC FIELD	: 17m gauss@0.1m
CHARGER	: Hybrid controlled charger
PROTECTION	: Low volt cut-off to prevent battery over discharge Incoming AC fuse and Battery DC fuse Tropical climate protection coating on hybrid control circuit
CONSTRUCTION	: Electrode galvanised sheet steel with epoxy powder coating 20mm \varnothing K/O hole. Fire Retardant Acrylic Opal diffuser.
CLASSIFICATION	: Co/A16, C90/A16
DIMENSION	: 285mm(L) x 95mm(W) x 310mm(H)
PACKING	: One unit per carton
CARTON / DIMENSION	: Double wall corrugated / 310mm(L) x 100mm(W) x 335mm(H)
COMPLIANCE	: CP 19:2000, SS263 : Part 2, IEC 598-2-22, SS 364
WARRANTY	: 1 Year

ORDERING INFORMATION

MODEL	LAMP USED	BATTERY CAPACITY	DURATION	GROSS WEIGHT
ETL 205-4LA	2 x 5W Halogen	4.5 AH	2 hrs \pm 10%	2.90 kg
ETL 205-7LA	2 x 5W Halogen	7.2 AH	3.5 hrs \pm 10%	3.40 kg
ETL 205-10LA	2 x 5W Halogen	10 AH	5.5 hrs \pm 10%	4.20 kg
ETL 205-4ND	2 x 5W Halogen	4.5 AH	2 hrs \pm 10%	2.80 kg
ETL 210-4LA	2 x 10W Halogen	4.5 AH	1 hr \pm 10%	2.90 kg
ETL 210-7LA	2 x 10W Halogen	7.2 AH	2 hrs \pm 10%	3.40 kg
ETL 210-10LA	2 x 10W Halogen	10 AH	3 hrs \pm 10%	4.20 kg
ETL 210-4ND	2 x 10W Halogen	4.5 AH	1 hr \pm 10%	2.80 kg

DIMENSION (mm)



Note: Due to continuous development and improvement, our company reserves the right to change specification without notice.



Certificate No. AJA047565



PSB Singapore



ISO9002-SAM-CAT-2016-028

