

SELF-CONTAINED WHITE LED EMERGENCY EXIT LIGHT



... is designed and specially equipped with a customised proprietary Hybrid IC. Compact and lightweight. Easy and fast installation with the thumb-press quick lock fastening system cuts down installation/maintenance time drastically.

Suitable for Factories, Schools, Sports Stadiums, Banks, Offices, Public Halls, Hospitals, Apartments, Warehouses, Carparks, etc.



TECHNICAL CHARACTERISTICS

INPUT VOLTAGE	: 240Vac 50/60Hz ± 10%, 115Vac 50/60Hz ± 10% or others
BATTERY	: 2.4V 2.5AH/4.5AH High temp rated Nickel Cadmium cells or others
LAMP USED	: SMT White LED
RATED PERIOD	: > 2 hrs, 3 hrs or others
MODE	: Maintained
OPERATION TEMPERATURE	: ta 40° C
POWER CONSUMPTION	: 4.6W
CHARGE MONITOR	: Super bright green LED 5mm Ø
RECHARGE PERIOD	: 16 ~ 24 hrs
EMERGENCY LUMINANCE	: > 8 cd/m ²
ELECTROMAGNETIC FIELD	: 17m gauss @ 0.1m
CHARGER	: Hybrid controlled charger
PROTECTION	: Low volt cut-off to prevent battery over discharge Incoming AC fuse and Battery DC fuse Tropical climate protection coating on hybrid control circuit
CONSTRUCTION	: Electrode galvanised sheet steel with epoxy powder coating 20mm Ø K/O hole, Fire Retardant Acrylic Opal diffuser
DIMENSION	: 370mm(L) x 80mm(W) x 165mm(H)
WEIGHT	: 2.60kg (Net) / 2.70kg (Gross)
PACKING	: One unit per carton
CARTON / DIMENSION	: Double wall corrugated / 390mm(L) x 100mm(W) x 180mm(H)
COMPLIANCE	: SS563-1:2010, SS563-2:2010/A1:2013. SSIEC 60598: PART 1: 2016.
WARRANTY	: 1 Year

ELS 115M-LED



IP 20




HYBRID IC CONTROLLED
SELF-CONTAINED EMERGENCY LIGHTING
SUPER BRIGHT SMT WHITE LED LUMINAIRE

ORDERING INFORMATION

LEGEND	MODEL
EXIT	ELS 115M-LED-00
◀EXIT	ELS 115M-LED-01
EXIT▶	ELS 115M-LED-02
◀EXIT▶	ELS 115M-LED-03

DIMENSION (mm)



(1) Other signs are available upon request
(2) Colours are available upon request

Note: Due to continuous development and improvement, our company reserves the right to change specification without notice.



ISO9001:2015-SAM-CAT-2018-009